



2018~2019

CAC

T1 50Hz
R410A



藏 天花式 - 定頻淨冷型 U 系列

Cassette Type



產品規格

型號 室內機 面板 室外機	製冷量	電源		輸入功率 (冷)	能源效益	出風量	運轉噪音		尺寸			淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	COP	室內機 CMH	室內機 (H/M/L) dB(A)	室外機 dB(A)	室內機 HxWxD (mm)	面板 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
GUD50T/A-K TF05 GUL50W/A-K	4900 16720	1 50	220-240V	1600	3.06	700	44	50	260 H 570 W 570 D	47.5 H 620 W 620 D	545 H 761 W 257 D	17	37	Φ1/2	Φ1/4	30	15
GU71T/A-K TF06 GUL71W/A-K	7100 24230	1 50	220-240V	2350	3.02	1250	46	53	240 H 840 W 840 D	52 H 950 W 950 D	698 H 892 W 340 D	30	53	Φ5/8	Φ3/8	30	15
GU100T/A-K TF06 GUL100W/A-M	10300 35100	3 50	380-415V	3500	2.94	1600	52	54	240 H 840 W 840 D	52 H 950 W 950 D	790 H 920 W 370 D	30	68	Φ5/8	Φ3/8	30	20
GU125T/A-K TF06 GUL125W/A-M	12000 40900	3 50	380-415V	4150	2.89	1600	52	57	240 H 840 W 840 D	52 H 950 W 950 D	820 H 940 W 460 D	33	93	Φ5/8	Φ3/8	50	30
GU140T/A-K TF06 GUL140W/A-M	14100 48100	3 50	380-415V	5800	2.43	2000	54	57	290 H 840 W 840 D	52 H 950 W 950 D	820 H 940 W 460 D	34	93	Φ5/8	Φ3/8	50	30
GU160T/A-K TF06 GUL160W/A-M	15000 54600	3 50	380-415V	5200	2.88	2000	55	56	290 H 840 W 840 D	52 H 950 W 950 D	820 H 940 W 460 D	34	95	Φ5/8	Φ3/8	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



風喉式 - 定頻淨冷型 U 系列

Duct Type

GREE 格力
格力商用式空調系列



產品規格

型號 室內機 室外機	製冷量		電源		輸入功率 (冷)	能源效益	出風量	運轉噪音		尺寸		淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	COP	室內機 CMH	室內機 (H/M/L) dB(A)	室外機 dB(A)	室內機 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m	
GUD50PHS/A-K GUL50W/A-K	5000 16720	1 50	220-240V	1600	3.13	900	41	50	300 H 700 W 700 D	545 H 761 W 257 D	32	37	Φ1/2	Φ1/4	30	15	
GUD71PHS/A-K GUL71W/A-K	7200 24230	1 50	220-240V	2400	3	1250	48	53	300 H 700 W 700 D	698 H 892 W 340 D	33	53	Φ5/8	Φ3/8	30	15	
GUD100PHS/A-K GUL100W/A-M	10300 35100	3 50	380-415V	3500	2.94	1650	44	54	300 H 1000 W 700 D	790 H 920 W 370 D	41	68	Φ5/8	Φ3/8	30	20	
GUD125PHS/A-K GUL125W/A-M	12500 40900	3 50	380-415V	4250	2.94	2000	46	57	300 H 1000 W 700 D	820 H 940 W 460 D	43	93	Φ5/8	Φ3/8	50	30	
GUD140PHS/A-K GUL140W/A-M	14100 48100	3 50	380-415V	5550	2.54	2400	48	57	300 H 1400 W 700 D	820 H 940 W 460 D	58	93	Φ3/8	Φ3/8	50	30	
GUD160PHS/A-K GUL160W/A-M	16000 54600	3 50	380-415V	5400	2.96	2900	48	56	300 H 1400 W 700 D	820 H 940 W 460 D	60	95	Φ3/8	Φ3/8	50	30	

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



樓底式 - 定頻淨冷型 U 系列

Cassette Type



產品規格

型號 室內機 室外機	製冷量	電源		輸入功率 (冷)	能源效益	出風量	運轉噪音		尺寸		淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	COP	室內機 CMH	室內機 (H/M/L) dB(A)	室外機 dB(A)	室內機 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
GU50ZD/A-K GUL50W/A-K	5000 17100	1 50	220-240V	1650	3.03	700	41	50	870 H 665 W 235 D	545 H 761 W 257 D	25	37	Φ1/2	Φ1/4	30	15
GU71ZD/A-K GUL71W/A-K	7200 24500	1 50	220-240V	2400	2.96	1400	47	53	1200 H 665 W 235 D	698 H 892 W 340 D	33	58	Φ5/8	Φ3/8	30	15
GU100ZD/A-K GUL100W/A-M	10300 35100	3 50	380-415V	3500	2.94	1700	51	54	1200 H 665 W 235 D	790 H 920 W 370 D	36	68	Φ5/8	Φ3/8	30	20
GU125ZD/A-K GUL125W/A-M	12000 40900	3 50	380-415V	4100	2.93	1700	51	57	1200 H 665 W 235 D	820 H 940 W 460 D	37	93	Φ5/8	Φ3/8	50	30
GU140ZD/A-K GUL140W/A-M	14100 48100	3 50	380-415V	5500	2.56	2200	54	57	1570 H 665 W 235 D	820 H 940 W 460 D	43	93	Φ5/8	Φ3/8	50	30
GU160ZD/A-K GUL160W/A-M	16000 54600	3 50	380-415V	5300	3.02	2500	53	56	1570 H 665 W 235 D	820 H 940 W 460 D	45	95	Φ5/8	Φ3/8	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



藏天花式 - 定頻冷暖型 H 系列

Cassette Type

GREE 格力
格力商用式空調系列



產品規格

型號 室內機 面板 室外機	製冷量 / 暖量	電源		輸入功率 (冷 / 暖)	能源效益 (冷 / 暖)	出風量	運轉噪音			尺寸			淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	EER COP	室內機 CMH CFM	室內機 (H/M/L) dB(A)	室外機 dB(A)		室內機 HxWxD (mm)	面板 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
GKH12K3HI TC03 GUHN12NK3HO	3550 / 3700 12100 / 12600	1 50	220-240V	1330 / 1200	2.69 3.08	560 330	40/38/35	52		240 H 665 W 595 D	50 H 670 W 670 D	540 H 848 W 320 D	19.5	33.5	Φ1/4	Φ1/2	20	15
GKH18K3HI TC03 GUHN18NK3HO	5000 / 5400 17100 / 18400	1 50	220-240V	2000 / 1900	2.5 2.84	720 423	49/47/46	56		240 H 665 W 595 D	50 H 670 W 670 D	700 H 890 W 380 D	20	53	Φ1/2	Φ1/4	20	15
GKH24K3HI TC04 GUHN24NK3HO	7000 / 7600 23900 / 25900	1 50	220-240V	2500 / 2300	2.8 3.3	1450 853	48/47/46	54		240 H 840 W 840 D	60 H 950 W 950 D	700 H 890 W 380 D	27	61	Φ5/8	Φ3/8	30	15
GKH30K3HI TC04 GUHN30NK3HO	29000 / 33400 9000 / 30700	1 50	220-240V	2700 / 2600	3.15 3.46	1500 883	50/49/48	59		240 H 840 W 840 D	60 H 950 W 950 D	790 H 980 W 425 D	27	69	Φ5/8	Φ3/8	30	15
GKH36K3HI TC04 GUHN36NM3HO	10000 / 11500 34100 / 39200	3 50	380-415V	3500 / 3300	2.86 3.48	1650 971	47/46/43	60		320 H 840 W 840 D	60 H 950 W 950 D	790 H 980 W 425 D	32	69	Φ3/4	Φ3/8	30	15
GKH42K3HI TC04 GUHN42NM3HO	12000 / 13500 40900 / 46100	3 50	380-415V	4200 / 4000	2.86 3.38	1650 971	47/46/43	60		320 H 840 W 840 D	60 H 950 W 950 D	1100 H 1020 W 450 D	32	100	Φ3/4	Φ1/2	50	30
GKH48K3HI TC04 GUHN48NM3HO	14100 / 15000 48100 / 51200	3 50	380-415V	4800 / 4900	2.94 3.06	1650 971	47/46/43	60		320 H 840 W 840 D	60 H 950 W 950 D	1100 H 1020 W 450 D	33	103	Φ3/4	Φ1/2	50	30
GKH60K3HI TC04 GUHN60NM3HO	15000 / 16800 51200 / 57300	3 50	380-415V	5300 / 5200	2.83 3.23	1800 1059	51/49/47	61		290 H 840 W 840 D	60 H 950 W 950 D	1350 H 980 W 410 D	37	118	Φ3/4	Φ1/2	50	30

備註：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



風喉式 - 定頻冷暖型 H 系列

Duct Type



產品規格

型號 室內機 室外機	製冷量 / 暖量	電源		輸入功率 (冷 / 暖)	能源效益 (冷 / 暖)	出風量	運轉噪音		尺寸		淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	COP	室內機 CMH CFM	室內機 (H/M/L) dB(A)	室外機 dB(A)	室內機 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
GFH12K3HI GUHN12NK3HO	3600 / 3700 12300 / 12600	1 50	220-240V	1350 / 1300	2.67 2.85	560 330	34/30/26	52	200 H 700 W 485 D	540 H 848 W 320 D	18.5	33.5	Φ1/4	Φ1/2	20	15
GFH18K3HI GUHN18NK3HO	5000 / 5400 17100 / 18400	1 50	220-240V	2000 / 1900	2.5 2.84	720 423	33/30/29	56	275 H 1015 W 720 D	700 H 890 W 380 D	32	53	Φ1/2	Φ1/4	20	15
GFH24K3HI GUHN24NK3HO	7000 / 7400 23900 / 25200	1 50	220-240V	2500 / 2300	2.8 3.22	1260 742	38/34/32	54	270 H 1260 W 555 D	700 H 890 W 380 D	33	61	Φ5/8	Φ3/8	30	15
GFH30K3HI GUHN30NK3HO	8300 / 8800 28300 / 30000	1 50	220-240V	2800 / 2700	2.96 3.26	1400 824	46/45/44	59	270 H 1260 W 555 D	790 H 980 W 425 D	34	69	Φ5/8	Φ3/8	30	15
GFH36K3HI GUHN36NM3HO	10000 / 11500 34100 / 39200	3 50	380-415V	3600 / 3300	2.78 3.48	2100 1235	48/46/44	60	290 H 1230 W 790 D	790 H 980 W 425 D	46	69	Φ3/4	Φ3/8	30	15
GFH42K3HI GUHN42NM3HO	12000 / 13500 40900 / 46100	3 50	380-415V	4400 / 4050	2.73 3.33	2100 1236	48/46/44	60	290 H 1230 W 790 D	1100 H 1020 W 450 D	46	100	Φ3/4	Φ1/2	50	30
GFH48K3HI GUHN48NM3HO	14100 / 15200 48100 / 51900	3 50	380-415V	5000 / 4700	2.82 3.23	2300 1354	52/50/50	60	290 H 1230 W 790 D	1100 H 1020 W 450 D	53	103	Φ3/4	Φ1/2	50	30
GFH62K3HI GUHN60NM3HO	16000 / 18000 54600 / 61400	3 50	380-415V	5600 / 5500	2.86 3.27	2500 1471	52/49/49	61	330 H 1235 W 830 D	1350 H 980 W 410 D	56	118	Φ3/4	Φ1/2	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



樓底式 - 定頻冷暖型 H 系列

GREE 格力
格力商用式空調系列

Floor Ceiling Type



產品規格

室內機 室外機	型號	製冷量 / 暖量		電源		輸入功率 (冷 / 暖)	能源效益 (冷 / 暖)	出風量	運轉噪音			尺寸		淨重		管道連接		配管長度	
		Watt BTU/h		Phase Hz	V	W	COP	室內機 CMH CFM	室內機 (H/M/L) dB(A)	室外機 dB(A)		室內機 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
	GTH12K3HI GUHN12NK3HO	3600 / 3700 12300 / 12600		1 50	220-240V	1350 / 1300	2.67 2.85	700 412	34/30/23	52		665 H 1200 W 235 D	540 H 848 W 320 D	25	33.5	Φ1/4	Φ1/2	20	15
	GTH18K3HI GUHN18NK3HO	5500 / 5700 18800 / 19400		1 50	220-240V	2000 / 2000	2.75 2.85	1000 589	37/35/33	56		665 H 1200 W 235 D	700 H 890 W 380 D	31	53	Φ1/2	Φ1/4	25	15
	GTH24K3HI GUHN24NK3HO	7200 / 8200 24600 / 28000		1 50	220-240V	2500 / 2400	2.88 3.42	1400 824	46/44/40	54		665 H 1200 W 235 D	700 H 890 W 380 D	32	61	Φ5/8	Φ3/8	30	15
	GTH30K3HI GUHN30NK3HO	8500 / 9800 29000 / 33400		1 50	220-240V	2800 / 2800	3.04 3.5	1500 883	48/46/43	59		665 H 1200 W 235 D	790 H 980 W 425 D	32	69	Φ5/8	Φ3/8	30	15
	GTH36K3HI GUHN36NM3HO	10600 / 11800 36200 / 40300		3 50	380-415V	3600 / 3600	2.94 3.28	1600 942	51/50/49	60		665 H 1200 W 235 D	790 H 980 W 425 D	36	69	Φ3/4	Φ3/8	30	15
	GTH42K3HI GUHN42NM3HO	12000 / 13200 40900 / 45000		3 50	380-415V	4300 / 4100	2.79 3.22	1650 971	41/50/49	60		665 H 1200 W 235 D	1100 H 1020 W 450 D	38	100	Φ3/4	Φ1/2	50	30
	GTH48K3HI GUHN48NM3HO	14200 / 16000 48500 / 54600		3 50	380-415V	5000 / 4700	2.84 3.4	2400 1412	55/53/52	60		665 H 1570 W 235 D	1100 H 1020 W 450 D	46	103	Φ3/4	Φ1/2	50	30
	GTH62K3HI GUHN60NM3HO	15800 / 18200 53900 / 62100		3 50	380-415V	5400 / 5450	2.87 3.34	2400 1412	55/53/52	61		665 H 1570 W 235 D	1350 H 980 W 410 D	46	118	Φ3/4	Φ1/2	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



藏 天花式 - 變頻冷暖型 F 系列

Cassette Type



產品規格

型號 室內機 面板 室外機	製冷量 / 暖量	電源		輸入功率 (冷 / 暖)	能源效益 (冷 / 暖)	出風量	運轉噪音			尺寸			淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	COP	室內機 CMH CFM	室內機 (H/M/L) dB(A)	室外機 dB(A)		室內機 HxWxD (mm)	面板 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
GKH12K3FI Panel GUHD12NK3FO	3500 / 3800 11942 / 12966	1 50	220-240V	1090 / 1050	3.21 / 3.62	700 412	45/41/36	52		240 H 596 W 596 D	50 H 670 W 670 D	540 H 848 W 320 D	20	34	Φ3/8	Φ1/4	20	15
GKH18K3FI Panel GUHD18NK3FO	5000 / 5500 17060 / 18766	1 50	220-240V	1600 / 1580	3.13 / 3.48	760 447	46/44/37	56		240 H 596 W 596 D	50 H 670 W 670 D	700 H 955 W 396 D	20	47	Φ1/2	Φ1/4	20	15
GKH24K3FI Panel GUHD24NK3FO	7000 / 8000 23884 / 27296	1 50	220-240V	2180 / 2210	3.21 / 3.62	1300 765	46/42/38	57		240 H 840 W 840 D	60 H 950 W 950 D	790 H 980 W 427 D	26	67	Φ5/8	Φ3/8	30	15
GKH30K3FI Panel GUHD30NK3FO	8300 / 9200 28320 / 31390	1 50	220-240V	2670 / 2570	3.11 / 3.58	1500 883	48/45/40	58		320 H 840 W 840 D	60 H 950 W 950 D	790 H 980 W 427 D	31	71	Φ5/8	Φ3/8	30	15
GKH36K3FI Panel GUHD36NM3FO	10000 / 12000 34120 / 40944	3 50	380-415V	3120 / 3320	3.21 / 3.6	1860 1095	49/46/43	63		320 H 840 W 840 D	60 H 950 W 950 D	1100 H 1107 W 440 D	31	98	Φ5/8	Φ3/8	30	15
GKH42K3FI Panel GUHD42NM3FO	11000 / 12500 37532 / 42650	3 50	380-415V	3900 / 3800	2.82 / 3.29	1860 1095	49/46/43	61		320 H 840 W 840 D	60 H 950 W 950 D	1349 H 958 W 412 D	31	108	Φ5/8	Φ3/8	50	30
GKH48K3FI Panel GUHD48NM3FO	14000 / 16000 47768 / 54592	3 50	380-415V	5150 / 4500	2.72 / 3.56	2300 1354	52/47/41	59		290 H 910 W 910 D	65 H 1040 W 1040 D	1349 H 958 W 412 D	43	114	Φ5/8	Φ3/8	50	30
GKH60K3FI Panel GUHD60NM3FO	16000 / 17000 54592 / 58004	3 50	380-415V	5700 / 4700	2.81 / 3.62	2400 1412	53/47/41	63		290 H 910 W 910 D	65 H 1040 W 1040 D	1365 H 1085 W 427 D	43	126	Φ3/4	Φ3/8	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



風喉式 - 變頻冷暖型 F 系列

Duct Type

GREE 格力
格力商用式空調系列



產品規格

室內機 室外機	型號	製冷量 / 暖量		電源		輸入功率 (冷 / 暖)	能源效益 (冷 / 暖)	出風量	運轉噪音			尺寸		淨重		管道連接		配管長度	
		Watt BTU/h		Phase Hz	V	W	COP	室內機 CMH CFM	室內機 (H/M/L) dB(A)	室外機 dB(A)		室內機 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
	GFH09K3FI GUHD09NK3FO	2700 / 2900 9212 / 9895		1 50	220-240V	840 / 800	3.21 / 3.63	650 383	34/28/26	52		250 H 925 W 665 D	540 H 848 W 320 D	27	34	Φ3/8	Φ1/4	20	15
	GFH12K3FI GUHD12NK3FO	3500 / 3800 11942 / 12966		1 50	220-240V	1170 / 1050	2.99 / 3.62	750 441	36/34/28	52		266 H 1037 W 721 D	540 H 848 W 320 D	33	34	Φ3/8	Φ1/4	20	15
	GFH18K3FI GUHD18NK3FO	5000 / 5600 17060 / 19107		1 50	220-240V	1550 / 1550	3.23 / 3.61	1000 589	39/36/28	56		266 H 1037 W 721 D	700 H 955 W 396 D	33	47	Φ1/2	Φ1/4	20	15
	GFH24K3FI GUHD24NK3FO	7000 / 8000 23884 / 27296		1 50	220-240V	2180 / 2210	3.21 / 3.62	1400 824	46/44/40	57		268 H 1279 W 558 D	790 H 980 W 427 D	34	67	Φ5/8	Φ3/8	30	15
	GFH30K3FI GUHD30NK3FO	8300 / 9200 28320 / 31390		1 50	220-240V	2670 / 2570	3.11 / 3.58	1400 824	46/44/40	58		268 H 1279 W 558 D	790 H 980 W 427 D	34	71	Φ5/8	Φ3/8	30	15
	GFH36K3FI GUHD36NM3FO	10000 / 12000 34120 / 40944		3 50	380-415V	3120 / 3320	3.21 / 3.61	2100 1236	52/48/44	63		290 H 1226 W 775 D	1100 H 1107 W 440 D	46	98	Φ5/8	Φ3/8	30	15
	GFH42K3FI GUHD42NM3FO	11500 / 13500 39238 / 46062		3 50	380-415V	4000 / 3900	2.88 / 3.46	2100 1236	52/48/44	61		290 H 1226 W 775 D	1349 H 958 W 412 D	46	108	Φ5/8	Φ3/8	50	30
	GFH48K3FI GUHD48NM3FO	14000 / 15500 47768 / 52886		3 50	380-415V	5100 / 4500	2.75 / 3.44	2400 1412	53/49/45	59		350 H 1340 W 750 D	1349 H 958 W 412 D	56	114	Φ5/8	Φ3/8	50	30
	GFH60K3FI GUHD60NM3FO	16000 / 16500 54592 / 56298		3 50	380-415V	5600 / 4570	2.86 / 3.61	3000 1766	56/54/49	63		350 H 1340 W 750 D	1365 H 1085 W 427 D	57	126	Φ3/4	Φ3/8	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



樓底式 - 變頻冷暖型 F 系列

Floor Ceiling Type



產品規格

型號 室內機 室外機	製冷量 / 暖量	電源		輸入功率 (冷 / 暖)	能源效益 (冷 / 暖)	出風量	運轉噪音		尺寸		淨重		管道連接		配管長度	
	Watt BTU/h	Phase Hz	V	W	COP	室內機 CMH CFM	室內機 (H/M/L) dB(A)	室外機 dB(A)	室內機 HxWxD (mm)	室外機 HxWxD (mm)	室內機 kg	室外機 kg	氣體管 inch	液體管 inch	最長 (單程) m	最高 (單程) m
GTH09K3FI GUHD09NK3FO	2700 / 2900 9212 / 9895	1 50	220-240V	840 / 800	3.21 / 3.63	600 353	29/26/24	52	225 H 1220 W 700 D	540 H 848 W 320 D	38	34	Φ3/8	Φ1/4	20	15
GTH12K3FI GUHD12NK3FO	3500 / 3800 11942 / 12966	1 50	220-240V	1090 / 1050	3.21 / 3.62	700 412	33/30/27	52	225 H 1220 W 700 D	540 H 848 W 320 D	39	34	Φ3/8	Φ1/4	20	15
GTH18K3FI GUHD18NK3FO	5000 / 5600 17060 / 19107	1 50	220-240V	1550 / 1550	3.22 / 3.61	1000 589	42/38/32	56	225 H 1220 W 700 D	700 H 955 W 396 D	39	47	Φ1/2	Φ1/4	20	15
GTH24K3FI GUHD24NK3FO	7000 / 8000 23884 / 27296	1 50	220-240V	2180 / 2210	3.21 / 3.6	1200 706	48/46/40	57	225 H 1220 W 700 D	790 H 980 W 427 D	40	67	Φ5/8	Φ3/8	30	15
GTH30K3FI GUHD30NK3FO	8500 / 9200 29002 / 31390	1 50	220-240V	2670 / 2570	3.18 / 3.58	1500 883	46/44/38	58	245 H 1420 W 700 D	790 H 980 W 427 D	48	71	Φ5/8	Φ3/8	30	15
GTH36K3FI GUHD36NM3FO	10000 / 12000 34120 / 40944	3 50	380-415V	3120 / 3320	3.21 / 3.61	1900 1118	53/51/46	63	245 H 1420 W 700 D	1100 H 1107 W 440 D	48	98	Φ5/8	Φ3/8	30	15
GTH42K3FI GUHD42NM3FO	11500 / 13500 39238 / 46062	3 50	380-415V	3900 / 3740	2.95 / 3.61	1900 1118	54/52/47	61	245 H 1420 W 700 D	1349 H 958 W 412 D	50	108	Φ5/8	Φ3/8	50	30
GTH48K3FI GUHD48NM3FO	14000 / 16000 47768 / 54592	3 50	380-415V	5000 / 4500	2.80 / 3.56	2300 1354	55/50/46	59	245 H 1700 W 700 D	1349 H 958 W 412 D	59	114	Φ5/8	Φ3/8	50	30
GTH60K3FI GUHD60NM3FO	16000 / 17000 54592 / 58004	3 50	380-415V	5750 / 4700	2.78 / 3.62	2500 1471	56/52/46	63	245 H 1700 W 700 D	1365 H 1085 W 427 D	59	126	Φ3/4	Φ3/8	50	30

備注：

1. 上述製冷量是根據以下的環境量度的：

- 室內環境：27°C (81°F) DB/19°C (66.6°F) WB;
- 室外環境：35°C (95.4°F) DB/24°C (75.6°F) WB;

* 產品設計及規格如有任何修改，將不作另行通知



Comfortable & Healthy

- 
Vertical swing
 Air discharge flaps can automatic move vertically for efficient air and temperature distribution throughout the room.
- 
Horizontal swing
 Air discharge Louvre can automatic move horizontally for efficient air and temperature distribution throughout the room.
- 
Turbo function
 To run with strong power and make you feel comfortable(cool or warm) quickly.
- 
Fresh air supply ventilation
 The unit can introduce a certain percentage of fresh air to satisfy the fresh air requirement.
- 
Comfortable sleeping mode
 The setting temperature and the indoor noise can be adjusted to a more comfortable level when you set the "sleeping mode".
- 
Quiet function
 Unit is ensured to operate with the lowest noise by ultra-low fan speed and auto adjustment according to system parameter.

High Efficiency & Energy Saving

- 
High efficiency
 The air conditioner is designed to high energy efficiency and to realize power saving.
- 
Intelligent defrosting
 It performs defrosting intelligently when necessary, thus improving heating efficiency and saving energy.
- 
Energy saving function
 When this function is activated, the temperature setting is only in limited range, so as to save energy.
- 
All DC inverter technology
 All motors adopt DC inverter technology, which greatly improves energy efficiency.

Reliability

- 
Auto clean
 After unit turn off , the indoor fan will keep running in low speed for a moment to dry the inner components and parts, in order to prevent mildew and keep users healthy.
- 
Self-diagnosis
 Malfunction codes are shown on the display panel for fast and easy maintenance when problem occur.
- 
Low voltage startup
 Unit is able to safely start when voltage is below standard.
- 
Low temperature heating
 Unit is able to start and operate in normal when the ambient temperature is lower than -20°C and heating capacity remains still.
- 
Modular operating
 Several units can operate together as modules, so that capacity output control is more precise, and also higher reliability.
- 
Comprehensive protection
 The unit is designed with various of protection functions to ensure the reliability.

Versatility

- 
High ESP
 The external static pressure range is higher, which ensures longer delivery distance for air to provide powerful cooling.
- 
Wide voltage range
 The unit can operate in a wide range of voltage, greatly reducing the impact of voltage fluctuation.
- 
Wide operation range
 Unit can operate in wide range, greatly reducing the ambient temperature limitation.
- 
Multi fan speed
 The fan can operate with multi speeds and satisfy different air flow volume requirement.
- 
Modular structure
 High efficiency compressor presents reliable performance.

Control

- 
24 hour timer
 Unit can be set to turn on or turn off at anytime in a day.(The timing interval is 5-minute.)
- 
Weekly timer
 Unit can be set to start heating or cooling anytime on a daily or weekly basis.
- 
°C/°F switch
 Under status of unit off, press MODE and "+" buttons simultaneity to switch °C/°F.
- 
Clock display
 Time is shown on remote controller .
- 
Child lock
 It avoids child's wrong operation on the remote controller.
- 
Key-card control
 The Key-card control function is specially designed for the hotel rooms. By removing the key-card the air conditioner, it can be automatically switched to stand-by status.
- 
Centralized control
 Starts, stops and regulates the air conditioner from a distance.
- 
Long-distance monitoring
 Long-distance monitoring enables the unit to be controlled and monitored from a long distance.
- 
Shield function
 Remote control the indoor unit and shield the functions of wired controller which include ON/OFF, temp or mode setting, energy-saving function, etc.
- 
Human engineering operation
 Adopts the technologies of auto addressing, non-polar communication and auto debugging, which improves project efficiency.
- 
Floor Heating Debugging



總代理



和記電業有限公司

香港新界荃灣海盛路 9 號有線電視大樓 33 樓 3302 室
Unit 2, 33/F., Cable TV Tower, No. 9 Hoi Shing Road,
Tsuen Wan, New Territories, Hong Kong
Tel: 852-2514 4700 Fax: 852-2525 1082

澳門板樟堂街 16F-16L 顯利商業中心 5 字樓 63 室
Rua de S. Domingos No.16L Centro Comercial
Hin Lei 5 Andar 63 room Macau
Tel: 853-2876 8155 Fax: 853-2876 8160